




COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC

Design for UAF Sustainable Village: **WILLOW HOUSE**

REMOTE wall with piling foundation



NOTE: The information contained in these documents was developed and published as a reference for specific climatic and site conditions. These documents are not a substitute for a detailed architectural plan set or site-specific engineering.


Any application of knowledge contained in this manual will need to consider site-specific issues including but not limited to applicable codes and structural design considerations for soil type, weather, and wind and snow load conditions. It is essential that a structural engineer review the plans to ensure they meet design criteria appropriate to the site.

This home has many elements that require specialized knowledge. We strongly recommend that skilled tasks, plumbing and electric work be done by professionals.

SUSTAINABLE VILLAGE AT UAF

SOUTHEAST PROTOTYPE HOME

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



7 SUSTAINABLE VILLAGE LOCATION



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC



ThotPro
STRUCTURAL ENGINEERING
www.thotpro.com

CODE REFERENCE

IBC 2006
UPC 2009
NEC 2011

LIST OF DRAWINGS

A0.0	COVER SHEET
C1.0	SITE PLAN
S4.0	S4.0
S4.1	S4.1
A2.1	1st FLOOR PLAN
A2.2	2nd FLOOR PLAN
A3.1	NORTH ELEVATION
A3.2	EAST ELEVATION
A3.3	SOUTH ELEVATION
A3.4	WEST ELEVATION
A4.0	BUILDING SECTIONS
A5.1	WINDOW SCHEDULE
A5.2	DOOR SCHEDULE
A6.0	DETAILS
P1.1	PLUMBING LAYOUT
E1.0	ELECTRICAL 1ST FLOOR
E1.1	ELECTRICAL 2ND FLOOR
E1.2	ELECTRICAL SERVICE
M1.0	MECHANICAL VENTILATION ...
M1.1	MECHANICAL VENTILATION ...
M1.2	SOLAR THERMAL SYSTEM
F100	FIRE SUPPRESSION
F101	FIRE SUPPRESSION

COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org




PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

COVER SHEET

A0.0

SHEET 1 OF total



4 SITE PLAN
SCALE: 1" = 20'

1 Site Map Entire Plat



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

SITE PLAN	
C1.0	
SHEET 3	OF total



5/14/2012

DESIGNED BY: CCHRC/Thotpro

DRAWN BY: FS

No.	Rev./Issue	Date

ThotPro
STRUCTURAL ENGINEERING
www.thotpro.com

CCHRC
1000 Fairbanks Street
P.O. Box 82489
Fairbanks, AK 99708-2489
(907) 457-3454
www.cchrc.org






**Sustainable
Village at UAF**
South East Home
Fairbanks, Alaska
ISSUED
5/14/2012

STRUCTURAL

S4.0

SHEET _____ OF _____





DESIGNED BY: CCHRC/ThotPro

DRAWN BY: FS

No.	Rev./Issue	Date

ThotPro
STRUCTURAL ENGINEERING
www.thotpro.com

COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC

1000 Fairbanks Street
P.O. Box 82489
Fairbanks, AK 99708-2489
(907) 457-3454
www.cchrc.org




PROJECT
Sustainable
Village at UAF
South East Home
Fairbanks, Alaska
ISSUED
5/14/2012

STRUCTURAL

S4.1



SHEET ____ OF ____



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date

COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development



1 2nd FLOOR PLAN



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date




COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

2nd FLOOR PLAN

A2.2

SHEET 8 OF total



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date




COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

NORTH ELEVATION

A3.1

SHEET 11 OF total



1 EAST ELEVATION

SCALE: 1/2" = 1'-0"

0

1

2

4

DESIGNED BY: CCHRC

DRAWN BY: Aa

REVISION NOTES

No.	Rev./Issue	Date

COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC

1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org


PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska

ISSUED
03/10/2012
Design Development

EAST ELEVATION

A3.2

SHEET 12 OF total



1

SOUTH ELEVATION

SCALE: 1/2" = 1'-0"

01'02'04'

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date




COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

SOUTH ELEVATION

A3.3

SHEET 13 OF total



1 WEST ELEVATION
SCALE: 1/2" = 1'-0"

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

WEST ELEVATION

A3.4

SHEET 14 OF total

Tashina Duttie1/15/13/Users/tashina/Desktop/SE_2013_01_14_Sustainable Village.pln



2 BUILDING SECTION

1 DETAIL

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC

1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org







PROJECT






Sustainable Village at
UAF South East Home
FS442
Fairbanks, Alaska
ISSUED 03/10/2012
Design Development

BUILDING SECTIONS

A4.0

SHEET 15 OF total

WINDOW SCHEDULE						
LAB...	TYPE	WIDTH	HEIGHT	HINGE	3D Front View	Quantity
01		6'	4'	FIXED		1
02		2'-6"	3'-8"	RIGHT		1
03	EGRESS	2'-6"	3'-8"	RIGHT		1
04		2'-6"	2'-6"	RIGHT		1
05		6'	4'	FIXED		1
06		6'	4'	FIXED		1

07	EGRESS	2'-6"	3'-8"	RIGHT		1
08	EGRESS	2'-6"	3'-8"	RIGHT		1
09	EGRESS	2'-6"	3'-8"	RIGHT		1
10	EGRESS	2'-6"	3'-8"	RIGHT		1
11		6'	4'	FIXED		1

SPECIFICATIONS

PVC, CASEMENT, TRIPLE-GLAZE WITH ARGON GAS
TOTAL THICKNESS 15-3/8" WITH 8-3/4" DISTANCE FROM FLANGE TO OUTSIDE AND 6-1/2"
DISTANCE FROM FLANGE TO INSIDE
INTERIOR RETURN AND EXTERIOR BOX-OUT TO BE PROVIDED
ROUGH OPENINGS 1/2" AROUND ENTIRE WINDOW FOR A TOTAL OF 1" IN BOTH DIMENSIONS







DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org







PROJECT
Sustainable Village at
UAF South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

WINDOW
SCHEDULE
A5.1
SHEET 17 OF total

DOOR SCHEDULE						
DOOR ...	TYPE	Quantity	WIDTH	HEIGHT	SWING	3D Front View
01	SOLID CORE INTERIOR DOOR	1	2'-8"	6'-8"	LHIS	
02	FIBERGLASS INSULATED DOOR	1	3'	6'-8"	LHIS	
03	FIBERGLASS INSULATED DOOR	1	3'	6'-8"	RHIS	
04	SOLID CORE INTERIOR DOOR	2	3'	6'-8"	LHIS	
05	SOLID CORE INTERIOR DOOR	1	2'-6"	6'-8"	LHOS	
06	SOLID CORE INTERIOR DOOR	1	2'-8"	6'-8"	RHIS	

1

SOUTHEAST UNIT DOOR SCHEDULE

07	SOLID CORE INTERIOR DOOR	1	2'-8"	6'-8"	LHIS	
08	SOLID CORE INTERIOR DOOR	1	3'	6'-8"	RHIS	
09	SOLID CORE INTERIOR DOOR	1	3'	6'-8"	LHIS	
10	SOLID CORE INTERIOR DOOR	1	2'-8"	6'-8"	LHOS	
11	BIFOLD CLOSET DOORS	1	5'	6'-8"		
12	SOLID CORE INTERIOR DOOR	1	2'-6"	6'-8"	LHOS	

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org



PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

DOOR SCHEDULE

A5.2

SHEET 18 OF total

1 DETAIL



DESIGNED BY:	CCHRC
DRAWN BY:	Aa
REVISION NOTES	
No.	Rev./Issue
	Date





COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

DETAILS

A6.0

SHEET 19 OF total



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date




COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

PLUMBING LAYOUT

P1.1

SHEET 20 OF total



KEY

- RECEPTACLE
- GFI RECEPTACLE
- SWITCH
- PILOT SWITCH
- 3-WAY SWITCH
- SMOKE DETECTOR
- TELEVISION
- TELEPHONE
- OUTDOOR LIGHT
- SCONCE LIGHT
- DOORBELL
- T8 FIXTURE
- EMERGENCY EXIT LIGHT
- 2-WAY EMERGENCY EXIT LIGHT
- CAN LIGHT
- CO DETECTOR

PANEL		100 AMP 1 ϕ 240V
1	DOWNSTAIRS BEDROOM	AFI
2	BATHROOM	
3	UPSTAIRS BEDROOMS	AFI
4	KITCHEN RECEPTACLES	
5	DOWNSTAIRS LIGHTS	AFI
6	KITCHEN RECEPTACLES +FRIDGE	
7	DOWNSTAIRS RECEPTACLES	AFI
8	RANGE	
9	NOOK RECEPTACLES, LIGHTS	AFI
10	RANGE	
11	HEAT TRACE AND STP	
12	HBH	
13	LIFT STATION	
14	MECH	
15		
16	HRV	
17		
18		
19		
20		

2 SOUTHEAST PANEL

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date

COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC

1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT Sustainable Village at UAF South East Home

FS442 Fairbanks, Alaska


ISSUED 03/10/2012 Design Development

ELECTRICAL 1ST FLOOR


E1.0

SHEET 21 OF total

Tashina Duttie 1/15/13 /Users/tashina/Desktop/SE_2013_01_14_Sustainable Village.pln



1 2nd FLOOR ELECTRICAL PLAN



KEY

- RECEPTACLE
- GFI RECEPTACLE
- SWITCH
- 3-WAY SWITCH
- SMOKE DETECTOR
- TELEVISION
- TELEPHONE
- OUTDOOR LIGHT
- SCONCE LIGHT
- DOORBELL
- VALENCE LIGHT
- EMERGENCY EXIT LIGHT
- CAN LIGHT

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER

CCHRC



1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development


ELECTRICAL 2ND
FLOOR

E1.1

SHEET 22 OF total



2 SITE PLAN



1 ELECTRICAL SERVICE

DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development

ELECTRICAL SERVICE		
E1.2		
SHEET	23	OF total

F:\New_Sales\Customer and Technical Support\TECH_SERVICES\Design Department\Tech Service\2012\Fire Safety\120417-40L Sustainable Village @ UAF - South.dwg 04/20/12 - 11:48 am

Markup Legend	
Delete Line	
Add Line	
Add Tee	
Add Elbow	
Add Coupling	
Add Head	
Delete Head	
Move Head	
Note: All revisions must be reviewed by Uponor	

Table F002-1

Multipurpose Fire Safety Systems

The Uponor Residential Fire Safety System is a residential fire protections system installed in combination with the cold side of the domestic potable water system. Only licensed contractors trained by Uponor can install this system.

What to do if Changes are Required

If any features or obstructions require the addition or deletion of sprinkler heads, or significant relocation of sprinkler heads, contact the Uponor Design Department to determine if observed changes require a redesign (888.594.7726).

MOST HYDRAULICALLY REMOTE HEADS			
	HEAD #	GPM	PRESSURE REQ'D AT STREET
1 HEAD	H.6	17	33.67
2 HEAD	H.17 & H.15	26.0028	39.67

- --- 16 RELIABLE Model RFC49RFC49 Concealed Pendent Sprinkler
K=4.9, 165F°, 3/8" Orifice, Maximum Spacing 16'x16'
Sprinkler head demand: 13 gpm @ 7.04
- --- 2 RELIABLE Model RFC49RFC49 Concealed Pendent Sprinkler
K=4.9, 165F°, 3/8" Orifice, Maximum Spacing 18'x18'
Sprinkler head demand: 17 gpm @ 12.03

12 1st Floor
6 2nd Floor
18 TOTAL

WELL CASING AND/OR TANK TO PROVIDE
260 GALS OF STORAGE. WELL PUMP TO
PROVIDE MINIMUM 26 GPM @ 45 PSI
AT MANIFOLD S.1

PUMP:
PRESSURE REQUIRED: 45psi
GPM REQUIRED: 26gpm



PUMP

15' OF
1" COPPER

ELEV=108'

1" AquaPEX
TO SYSTEM

(S.1)

ELEV=104'

1" FULL PORT
BALL VALVE


2

F100

WATER SERVICE DETAIL

NTS


SPRINKLER SYMBOL DEFINITION



SLOPED CEILING MAX. SLOPE OF 8:12
(33.7°) PITCH (MAY NOT APPLY)
SLOPED CEILING MAX. SLOPE OF 4:12
(18.4°) PITCH (MAY NOT APPLY)
MAXIMUM SPACING (TYP)
SPRINKLER MODEL (TYP)
HEAD SYMBOL (TYP)

COLOR/LINETYPE LEGEND

BLUE LINES= FEED TO FIXTURES (BATH, SHOWER, ETC.).
GREEN LINES= INTERLEVEL CONNECTIONS.
BLACK LINES= SPRINKLER HEAD TO SPRINKLER HEAD.
--- = 1/2" PIPE SIZE
--- = 3/4" PIPE SIZE
--- = 1" PIPE SIZE
--- = 1-1/4" PIPE SIZE
--- = 2" PIPE SIZE



1" INTERLEVEL CONNECTIONS
BETWEEN FLOORS

3

F100

SECOND LEVEL

1/4" = 1'-0"

1" AquaPEX

S.1 MAIN SHUT-OFF
VALVE LOCATION


1

F100

FIRST LEVEL

1/4" = 1'-0"

1st FLOOR PLAN



uponor

DISCLAIMER

THIS SERIES OF PLUMBING, HYDROHEATING/COOLING, SNOW AND MELTING SYSTEMS HAVE BEEN DESIGNED BY UPONOR, INC. TECHNICAL SERVICES - DESIGN DEPARTMENT. THEY HAVE BEEN PREPARED TO MEET PROFESSIONAL ENGINEERING STANDARDS AND REQUIREMENTS. UPONOR, INC. MAKES NO WARRANTY OF DESIGN OR PERFORMANCE. IT IS THE USER'S RESPONSIBILITY TO OBTAIN ALL NECESSARY PERMITS AND/OR FIRE CODES USED. REPORT ANY ERRORS AND/OR DESIGN CHANGES TO UPONOR, INC. IMMEDIATELY. UPONOR, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES THAT MAY RESULT FROM THE APPLICATION AND INTERPRETATION OF THESE DRAWINGS. SALES REP.

SUSTAINABLE VILLAGE AT UAF SOUTH
1000 FAIRBANKS ST.
FAIRBANKS AK 99709

SHEET DESCRIPTION
BASEMENT LEVEL

SHEET NUMBER

F100


TECHNICAL SERVICES - DESIGN DEPARTMENT
21900 DODD BLVD., LAKEVILLE, MN 55044
TEL: 888.594.7726
EMAIL: TECHNICAL_SERVICES@UPONOR.COM
WEB: WWW.UPONOR-USA.COM

CONTACT		CONTACT PH. NUMBER:		ALLIANCE ID:		PLOT DATE:		SHEET SCALE:		PROJECT NUMBER:		SQUARE FEET:	
DRAWN BY:	NEIL FINTELMAN	CONTACT PH. NUMBER:	907.457.3454	ALLIANCE ID:	#####	PLOT DATE:	4/17/12	SHEET SCALE:	1/4"=1'-0"	PROJECT NUMBER:	120417-40L	SQUARE FEET:	1024 SQ. FEET
CHECKED BY:	DAN HUBBARD	CERTIFICATION NUMBER:	115052	COMPANY:	ICCHRC	CONTACT:	AARON COOKE	REVISIONS					

AquaSAFE™ GENERAL NOTES:


1. THIS SYSTEM IS DESIGNED AS PER NFPA 13D 2010 EDITION AS A RESIDENTIAL MULTIPURPOSE SYSTEM. SECTION 3.3.9.3
2. UPONOR COMPANY RESERVES THE EXCLUSIVE RIGHTS TO ALL DETAILS AND DRAWINGS AS SHOWN ON THIS SHEET. THESE DETAILS AND DRAWINGS ARE PROPRIETARY INFORMATION OF UPONOR COMPANY AND UNAUTHORIZED USE MAY BE SUBJECT TO PROSECUTION TO THE FULL EXTENT OF THE LAW.
3. THE DESIGN OF THIS SYSTEM IS DICTATED BY SPECIFIC CEILING HEIGHTS AND ROOM SIZES. IT IS THE RESPONSIBILITY OF THE INSTALLING CONTRACTOR TO ENSURE THAT THE CONDITIONS SHOWN ON THESE PLANS ARE EXACTLY AS THEY EXIST IN THE FIELD. DEVIATIONS FROM THE DESIGN MAY CAUSE THE SYSTEM TO BE UNABLE TO CONTROL A FIRE. IF THE BUILDING CONSTRUCTION DIFFERS FROM THE FIRE SPRINKLER PLAN, CONTACT THE SYSTEM DESIGNER IMMEDIATELY.
4. THIS SYSTEM AND THE ACCOMPANYING HYDRAULIC CALCULATIONS ARE DESIGNED IN COMPLIANCE WITH NFPA 13D 2010 EDITION.
5. "STAND ALONE" OR "MULTIPURPOSE, WET PIPE" SYSTEMS ARE NOT PERMITTED TO USE ANTI-FREEZE.
6. MODIFICATIONS ARE PROHIBITED. SPRINKLERS THAT HAVE BEEN PAINTED, CAULKED, MODIFIED OR DAMAGED MUST BE REPLACED.
7. WATER SHUT OFF VALVE IS NOT PERMITTED.
8. OWNERS MANUAL MUST BE PROVIDED TO THE OWNER.
9. AT THE MAIN SHUT OFF VALVE, A TAG OR A SIGN STATING THE FOLLOWING IS REQUIRED; "WARNING, THE WATER SYSTEM FOR THIS HOME SUPPLIES FIRE SPRINKLERS THAT REQUIRE CERTAIN FLOWS AND PRESSURES TO FIGHT A FIRE. DEVICES THAT RESTRICT THE FLOW OR DECREASE THE PRESSURE OR AUTOMATICALLY SHUT OFF THE WATER TO THE FIRE SPRINKLER SYSTEM, SUCH AS WATER SOFTENERS, FILTRATION SYSTEMS AND AUTOMATIC SHUT OFF VALVES, **SHALL NOT** BE ADDED TO THIS SYSTEM WITHOUT REVIEW OF THE FIRE SPRINKLER SYSTEM BY A FIRE PROTECTION SPECIALIST. **DO NOT REMOVE THIS SIGN**".
10. ALL INTERIOR PIPING TO BE UPONOR "AquaPEX®" UNLESS NOTED.
11. UPONOR "AquaPEX" TUBING TO BE SUPPORTED PER NFPA 13D AND MANUFACTURER'S RECOMMENDATIONS.
12. MINIMUM SPACING BETWEEN SPRINKLERS IS 8'-0" REFER TO SPACING CHARTS FOR MAXIMUM SPACING BETWEEN SPRINKLERS AND FROM WALLS.
13. SPRINKLERS ARE NOT NECESSARILY CENTERED IN ROOMS DUE TO LIGHT FIXTURES OR OTHER CEILING MOUNTED OBSTRUCTIONS.
14. THE PLUMBING TIE IN CONNECTIONS ARE SCHEMATIC IN NATURE AND CAN BE INSTALLED OFF THE SPRINKLER LOOP ANYWHERE BETWEEN SPRINKLER TO SPRINKLER CONNECTION.
15. THIS SUGGESTED LAYOUT IS BASED UPON INFORMATION PROVIDED BY OTHERS. CHANGES IN CONSTRUCTION OR FIELD CONDITIONS MAY OCCUR WHICH MAY REQUIRE CHANGES TO THE LAYOUT. IT IS THE RESPONSIBILITY OF THE INSTALLER TO NOTIFY UPONOR TECHNICAL SERVICES OF SUCH CHANGES.
16. INSULATION GUIDE LINES PER NFPA 13D.
 - 8.3.1* WET PIPE SYSTEMS. A WET PIPE SYSTEM SHALL BE PERMITTED TO BE TO BE USED WHERE ALL PIPING IS INSTALLED IN AREAS MAINTAINED ABOVE 40°F, INCLUDING AREAS PROPERLY INSULATED TO MAINTAIN 40°F.
 - A.8.3.1 IN AREAS SUBJECT TO FREEZING, CARE SHOULD BE TAKEN IN UNHEATED ATTIC SPACES TO COVER SPRINKLER PIPING COMPLETELY WITH INSULATION. INSTALLATION SHOULD FOLLOW THE GUIDELINES OF THE INSULATION MANUFACTURER. FIGURE A.8.3.1(A) THROUGH FIGURE A.8.3.1(E) SHOW SEVERAL METHODS THAT CAN BE CONSIDERED.
19. NFPA 13D 8.6 LOCATION OF SPRINKLERS.
 - 8.6.1 SPRINKLERS SHALL BE INSTALLED IN ALL AREAS EXCEPT WHERE OMISSION IS PERMITTED BY 8.6.2 THROUGH 8.6.7.
 - 8.6.2 SPRINKLERS SHALL NOT BE REQUIRED IN BATHROOMS OF 55 FT² (5.1 M²) AND LESS
 - 8.6.3 SPRINKLERS SHALL NOT BE REQUIRED IN CLOTHES CLOSETS, LINEN CLOSETS, AND PANTRIES THAT MEET ALL OF THE FOLLOWING CONDITIONS:
 - (1) THE AREA OF THE SPACE DOES NOT EXCEED 24 FT² (2.2 M²).
 - (2) THE LEAST DIMENSION DOES NOT EXCEED 3 FT (0.9 M).
 - (3) THE WALLS AND CEILINGS ARE SURFACED WITH NONCOMBUSTIBLE OR LIMITED-COMBUSTIBLE MATERIALS AS DEFINED IN NFPA 220, STANDARD ON TYPES OF BUILDING CONSTRUCTION.
 - 8.6.4* SPRINKLERS SHALL NOT BE REQUIRED IN GARAGES, OPEN ATTACHED PORCHES, CARPORTS, AND SIMILAR STRUCTURES
 - A.8.6.4 ALTHOUGH NFPA 13D DOES NOT REQUIRE GARAGES TO BE SPRINKLERED, SOME AUTHORITIES HAVING JURISDICTION TAKE IT UPON THEMSELVES TO ADD THIS REQUIREMENT LOCALLY. IN SUCH CIRCUMSTANCES, RESIDENTIAL OR QUICK-RESPONCE SPRINKLERS WITH A TWO-SPRINKLER DESIGN IN THE GARAGE WITH THE SAME PIPING USED IN THE REST OF THE DWELLING MAY BE USED. IT IS RECOGNIZED THAT RESIDENTIAL SPRINKLERS HAVE NOT BEEN TESTED SPECIFICALLY FOR FIRES IN GARAGES, BUT FIELD EXPERIENCE HAS SHOWN THAT THE SPRINKLERS HELP TO ALERT OCCUPANTS TO THE FACT THAT THERE IS A FIRE, CAN REDUCE THE POSSIBILITY OF FLASHOVER, AND CAN IMPROVE THE CHANCES FOR OCCUPANTS TO ESCAPE.
 - 8.6.5 SPRINKLERS SHALL NOT BE REQUIRED IN ATTICS, PENTHOUSE EQUIPMENT ROOMS, ELEVATOR MACHINE ROOMS, CONCEALED SPACES DEDICATED EXCLUSICELY TO AND CONTAINING ONLY DWELLING UNIT VENTILATION EQUIPMENT, FLOOR/CEILING SPACES, ELEVATOR SHAFTS CRAWL SPACES, AND OTHER CONCEALED SPACES THAT ARE NOT USED OR INTENDED FOR LIVING PURPOSES AND DO NOT CONTAIN FUEL-FIRED EQUIPMENT.
 - 8.6.6 SPRINKLERS SHALL NOT BE REQUIRED IN COVERED UNHEATED PROJECTIONS OF THE BUILDING AT ENTRANCES/EXITS AS LONG AS THERE IS ANOTHER MEANS OF EGRESS FROM THE DWELLING UNIT.
 - 8.6.7 SPRINKLERS SHALL NOT BE REQUIRED FOR CEILING POCKETS THAT MEET THE FOLLOWING CONDITIONS:
 - (1) THE TOTAL VOLUME OF UNPROTECTED CEILING POCKET DOES NOT EXCEED 100 FT³ (2.83 M³).
 - (2) THE ENTIRE FLOOR UNDER THE UNPROTECTED CEILING POCKET IS PROTECTED BY THE SPRINKLERS AT THE LOWER CEILING ELEVATION.
 - (3) EACH UNPROTECTED CEILING POCKET IS SEPERATED FROM ANY ADJACENT UNPROTECTED CEILING POCKET BY A MINIMUM 10 FT (3.05 M) HORIZONTAL DISTANCE.
 - (4) THE INTERIOR FINISH OF THE UNPROTECTED CEILING POCKET IS NONCOMBUSTIBLE OR LIMITED-COMBUSTIBLE MATERIAL.
 - (5) SKYLIGHTS NOT EXCEEDING 32 FT² (2.97 M²) SHALL BE PERMITTED TO HAVE A PLASTIC COVER.

Flat Concealed Assembly Sprinkler Placement



Caution: Do not paint over the sprinklers cover plates. Paint may interfere with the heat sensitivity of the sprinkler, and disturbances may damage the sprinkler.

See General Notes 8.6.3 for Closet Requirements



Insulation Recommendations

In areas subject to freezing, care should be taken in unheated attic spaces to cover Uponor AquaPEX tubing completely with insulation. Insulation should follow the guidelines of the insulation manufacturer. See Uponor Document "**Uponor AquaSAFE Attic Insulation Guidelines**" for attic installation guidelines (Provided in Contractors Documents package or online at www.Uponorpro.com).

Extreme Temperature Installations

AquaSAFE Residential Fire Safety systems are often installed in attics or other areas exposed to temperature extremes of heat and/or cold. Follow the recommended extreme weather installation instructions to isolate and protect system components from extreme temperatures. Because this system also delivers domestic cold water directly to plumbing fixtures, Uponor highly recommends that you protect the tubing with adequate insulation in warm weather areas to minimize heating of the cold water supply.

Installation methods include, but are not limited to:

- Tenting over the fire sprinkler piping.
- Additional layers of batt insulation.
- Increased depth of blown-in insulation.

Caution: If you will be installing spray foam insulation, make sure to protect all components during application. Consult with the spray foam manufacturer to ensure compatibility with all products before application.

Consultation with local building officials is encouraged to ensure compliance with local building codes.


Bending PEX Tubing

The minimum bend radius of Uponor PEX tubing in any direction is six times the outside diameter (**6 x OD**). Bend supports are available for 3/8", 1/2", 3/4" and 1" Uponor AquaPEX tubing to facilitate 90-degree rigid bends.

Recommended Tubing Length Between Fittings	
Fitting Size	Minimum Tubing Length
3/8" ProPEX Fitting	2"
1/2" ProPEX Fitting	2 1/2"
3/4" ProPEX Fitting	3 1/2"
1" ProPEX Fitting	4 1/2"
1 1/4" ProPEX Fitting	5 1/2"

Standard Riser Assembly


In a multi-purpose system a single control valve controls both domestic and fire safety needs (see **Figure F001-9**).



Slope Guide			
Slope: Rise/Run	Pitch: Degrees	Slope: Rise/Run	Pitch: Degrees
0/12	0°	9/12	36.87°
1/12	4.76°	10/12	39.81°
2/12	9.46°	11/12	42.51°
3/12	14.04°	12/12	45°
4/12	18.43°	13/12	47.29°
5/12	22.62°	14/12	49.40°
6/12	26.57°	15/12	51.34°
7/12	30.26°	16/12	53.13°
8/12	33.69°	17/12	54.78°
		18/12	56.31°

NFPA 13D Table 7.5.5.3 Distances From Heat Sources

Heat Source	Ordinary Temp. 135°-170°	Intermediate Temp. 175°-225°
Side of Fireplace	36"	12"
Front of Fireplace	60"	36"
Wood Burning Stove	42"	12"
Kitchen Range	18"	9"
Wall Oven	18"	9"
Hot Air Flues	18"	9"
Uninsulated Heat Ducts	18"	9"
Uninsulated Hot Water Pipes	12"	6"
Side of Hot Air Diffuser	24"	12"
Front of Hot Air Diffuser	36"	18"
Hot Water Heater	6"	3"
Furnace	6"	3"
50W-250W Light Fixture	6"	3"
250W-499W Light Fixture	12"	6"



Tubing Support Spacing:

(Anchor AquaPEX Tubing Securely Enough to Support the Tubing, Yet Relaxed Enough to Allow the Tubing to Expand and Contract)

1. Along Horizontal Runs, Install Supports Every 32", if Horizontal Runs are Continuously Supported, Place Tubing Supports at Six-Foot Intervals.
2. Along Vertical Runs, Install Supports Every Four to Five Feet, at Each Floor and at a Mid-story Guide.

In-line Flow Test

The In-line Flow Test can be constructed on site. It performs a flow test to ensure proper system operation and flow (see **Figure F001-8**).




Figure F001-8

Flow Test

To ensure the system provides enough water for proper fire sprinkler performance, you should conduct a flow verification test.

Note: The NFPA 13D Installation Standard does not require flow verification.

Before performing a flow verification test, confirm the water pressures by contacting the Water and Sewer Department of your local city. Ensure the available water pressure matches the pressure used in the system design.

Note: The sprinkler plan indicates the most hydraulically remote sprinkler (or pair of sprinklers). For test requirements on other sprinklers, consult your local code.

Note: It is a good idea to notify the fire inspector at least 24 hours prior to performing a flow verification test. This may speed up the inspection process and eliminate the need to repeat the test for the inspector.

Note: See AquaSAFE Flow Test Instruction Sheet provided in the job packet submittal or online for more information on Flow Test Setup, Assembly, Performing the Test and Troubleshooting. If there are any questions please contact Uponor.

uponor

TECHNICAL SERVICES - DESIGN DEPARTMENT
21800 DOOD BLVD LAKESVILLE, MN 55044
TEL: 651.451.5000 FAX: 651.451.5001
EMAIL: TECHNICALSERVICES@UPONOR.COM
WEB: WWW.UPONOR-USA.COM

DISCLAIMER
THIS SERIES OF PLUMBING, FIREPROTECTION, MECHANICAL, ELECTRICAL, HEATING, VENTILATING, AIR-CONDITIONING, SNOW AND ICE MELTING AND/OR FIRE SPRINKLER TECHNICAL SERVICES HAVE BEEN DESIGNED BY UPONOR, INC. TECHNICAL SERVICES - DESIGN DEPARTMENT. THEY HAVE BEEN PREPARED TO MEET PROFESSIONAL STANDARDS OF CARE AND PRACTICE. THEY ARE NOT TO BE USED AS A WORK ASSOCIATED WITH THIS DESIGN. IT IS MANDATORY TO MAKE A CAREFUL CHECK OF THE SIZE, CALCULATIONS, MATERIALS, PLUMBING AND ELECTRICAL CODES, AND ANY OTHER APPLICABLE CODES AND TO DETERMINE IF THE DESIGN REQUIRES REVISION. IF ERRORS AND/OR CHANGES TO UPONOR'S DESIGN ARE REQUIRED, UPONOR'S DESIGN DEPARTMENT WILL BE NOTIFIED IMMEDIATELY. UPONOR'S DESIGN DEPARTMENT WILL FUNCTION IN ACCORDANCE WITH ALL APPLICABLE CODES AND STANDARDS. THERE IS NO WARRANTY WRITTEN, EXPRESSED OR IMPLIED, FOR DAMAGES THAT MAY RESULT FROM THE APPLICATION AND INCORPORATION OF THESE DRAWINGS.
SALES REP:


SUSTAINABLE VILLAGE AT UAF SOUTH
1000 FAIRBANKS ST.
FAIRBANKS AK 99709

DRAWN BY:	NEIL FINTELMAN	CONTACT PH. NUMBER:	907.457.3454
CHECKED BY:	DAN HUBBARD	ALLIANCE ID:	#####
CERTIFICATION LEVEL:	SET IV	PLOT DATE:	4/17/12
CERTIFICATION NUMBER:	115052	SHEET SCALE:	N.T.S.
COMPANY:	CCHRC	PROJECT NUMBER:	120417-40L
CONTACT:	AARON COOKE	SQUARE FEET:	1024 SQ. FEET
		REVISIONS	
NO.	DATE	DESCRIPTION	

SHEET DESCRIPTION
GENERAL NOTES
AND DETAILS


SHEET NUMBER

F001





CCHRC 1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

SHEET 24 OF total



1

MECHANICAL PLAN 2nd FLOOR



KEY

- RETURN AIR DIFFUSER
- SUPPLY AIR
- GRILLE DIRECTION

NOTE

WALL MOUNTED ADJUSTABLE DIFFUSER GRILLE 8" FROM THE FLOOR ON SUPPLY DUCT

DESIGNED BY:	CCHRC
DRAWN BY:	Aa
REVISION NOTES	
No.	Rev./Issue
	Date



COLD CLIMATE HOUSING RESEARCH CENTER
CCHRC
1000 FAIRBANKS STREET
P.O. BOX 82489
FAIRBANKS, AK 99708-2489
(907) 457-3454
www.cchrc.org

PROJECT
Sustainable Village at
UAF
South East Home
FS442
Fairbanks, Alaska
ISSUED
03/10/2012
Design Development


MECHANICAL
VENTILATION PLAN

M1.1

SHEET 25 OF total

1

Southeast Unit Solar Thermal Diagram



DESIGNED BY: CCHRC		
DRAWN BY: Aa		
REVISION NOTES		
No.	Rev./Issue	Date